

# FTXB-C

Energy efficiency

**A+**

It brings pleasant comfort instantly to your home. The flat, stylish front panel and its functions create great atmosphere on an affordable price level.

- › Flat, stylish front panel that fits universally in every interior
- › Vertical auto swing distributes the air & temperature evenly in the whole room
- › Whisper quiet operation provides a better comfort
- › The 24-hour timer gives you a greater flexibility throughout the day



Efficiency data		FTXB + RXB	20C + 20C	25C + 25C	35C + 35C	50C + 50C	60C + 60C	
Cooling capacity	Min./Nom./Max.	kW	1,3/2,0/2,6	1,3/2,5/3,0	1,3/3,3/3,8	1,6/5,5/6,2	1,8/6,2/6,5	
Heating capacity	Min./Nom./Max.	kW	1,3/2,5/3,5	1,3/2,8/4,0	1,3/3,5/4,8	1,2/5,6/6,6	1,2/6,4/7,1	
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A+					
		Pdesign	kW	2,00	2,50	3,30	5,48	6,23
		SEER		5,98	6,02	6,05	5,93	6,09
	Heating (Average climate)	Annual energy consumption	kWh	117	145	191	324	359
		Energy label	A+					
		Pdesign	kW	2,20	2,40	2,80	3,64	3,80
	SCOP/A		4,10	4,01	4,06	4,27	4,06	
	Annual energy consumption	kWh	751	838	966	1.195	1.311	

Technical data - Indoor unit			FTXB	20C	25C	35C	50C	60C
Dimensions	Unit	HeightxWidthxDepth	mm	283x770x216			310x1.065x224	
Air filter	Type	Removable/washable/mildew proof						Saranet
Sound pressure level	Cooling	Super high/High/Low/Silent operation	dBA	-/39/25/21	-/40/26/21	-/41/27/23	44/40/35/32	46/43/37/33
	Heating	Super high/High/Low/Silent operation	dBA	-/39/28/25	-/40/28/25	-/41/29/26	44/40/35/32	46/43/37/33

Technical data - Outdoor unit				RXB	20C	25C	35C	50C	60C
Dimensions	Unit	HeightxWidthxDepth	mm	550x658x275			753x855x328		
Sound pressure level	Cooling	High/Nom.	dBA	46/-		48/-		-/51	
	Heating	High/Nom.	dBA	47/-		48/-		-/51	
Operation range	Cooling	Ambient	Min.-Max.	°CDB -10~46					
	Heating	Ambient	Min.-Max.	°CWB -15~18					
Refrigerant	Type/Charge/GWP	Charge: kg/TCO <sub>2</sub> eq	R-410A/0,74/1,5/2.087,5			R-410A/1,0/2,1/2.087,5		R-410A/1,45/3,0/2.087,5	
Piping connections	Piping length	OU - IU	Max.	15		10		7,5	
		System	Chargeless	10		12		10	
		Level difference	IU - OU	12		10		10	
Current - 50Hz	Maximum fuse amps (MFA)		A	16			20		

